



301 ASPHALT ROOF & FOUNDATION COATING

TECHNICAL DATA SHEET



DESCRIPTION:


APOC 301 Asphalt Roof & Foundation Coating is water-based, liquid-applied and designed to restore worn asphalt roof surfaces (built-up roofs, modified bitumen, existing asphalt coatings) and dampproof exterior foundation walls. Product can be coated with a reflective coating 7 days after initial application. Can also be used to seal and protect underground wood footings and metal surfaces.

PREPARATION:

All surfaces must be clean and free of surface rust, dust and any other foreign matter or debris. Pressure washing entire surface is recommended (use only a wide fan tip - do not allow stream to tear into roof surface). Patch all cracks or seams with APOC 109 Asphalt Roof Cement and reinforce with APOC 470 Reinforcing Fabric or APOC Incredible® Tape. This product can be applied to slightly damp surfaces, but do not apply to wet surfaces or if rain is expected within 24-48 hours dependent on temperature, humidity and direct sunlight. On foundations apply only over concrete and masonry that has properly cured and set. New concrete needs to cure 28-30 days before coating.

APPLICATION:

Use brush or roller to spread across surface of foundation or roof. Apply when temperatures are a minimum of 55°F (12°C) and rising. Do not use on TPO, PVC, EPDM, Hypalon, or other single ply/synthetic surfaces.



TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Solids Weight	> 45%
Solids Volume	> 43%
Viscosity	10,000 - 18,000 cps
Density	8.76 lb/gal
Remulsibility	None
Cold Temp. Flexibility	@ 18°C = Pass
Application Temperature	55°F - 110°F
Skin Time <small>(50% Relative Humidity, 70°F)</small>	2-6 hours
Full Cure <small>(50% Relative Humidity, 70°F)</small>	24-48 hours

Approx. Shipping Weights:

(Note: All approx. weights include container)

4.75 gallons (18L)

44 lb.

VOC: <10 g/L (regulatory)

COVERAGE RATE:

Approximately 350 sq. ft./5 gal.

Coverage will vary depending on texture and porosity of surface. Two coats are recommended.

CLEAN-UP:

Clean up wet coating with water before it dries. Tools should be cleaned with paint thinner or mineral spirits.

PRECAUTIONS:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves, protective clothing, eye protection and face protection. Avoid breathing mist/vapors/spray. Wash all exposed external body areas thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. KEEP OUT OF REACH OF CHILDREN. If exposed or concerned get medical advice. IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/container to authorized hazardous or special waste collection point and in accordance with applicable local/national/regional/international regulations. Do not use in drinking water or food systems. SEE SAFETY DATA SHEET.

STORAGE & HANDLING PRECAUTIONS:

When transporting this product, ensure that lid is tight and pail is secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 100°F (37°C). This manufacturer also disclaims liability for flat surface application where poor drainage or ponding water may prevail. Do not reuse empty containers.

Gardner-Gibson, Inc.

4161 East 7th Avenue. Tampa, FL 33605
1.800.237.1155 | www.icpgroup.com | C25



PERSONAL PROTECTIVE EQUIPMENT



EYEWEAR



PROTECTIVE CLOTHING



GLOVES

WARRANTY AND DISCLAIMER:

APOC warrants product to be free of material defects for a period of 1 year, the "Warranty Period", from the date of purchase. Product must be applied in accordance with the proper application procedures, and for the intended use as stated on the label. Proper preparation and drying conditions must be observed to achieve correct results. Should a product not perform as stated, APOC shall, within its sole discretion and upon receipt of purchaser's timely written notice within the Warranty Period, provide replacement product to repair the affected area or prorate a portion of the purchase price of the defective product based on the claim period. This limited warranty does not cover labor or installation costs, consequential damages or incidental damages. Under no circumstances will the company be liable for any amount in excess of the product purchase price. Contact company below to request a refund with purchase receipt. There are no warranties which extend beyond the description on the face hereof. THIS LIMITED WARRANTY IS THE SOLE WARRANTY PROVIDED BY APOC TO THE PURCHASER. THERE IS NO IMPLIED WARRANTY OF MERCHANTABILITY OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE PROVIDED WITH THIS PRODUCT.