

POLYSET® MULTIPURPOSE CLEANER

TECHNICAL DATA SHEET



PERSONAL PROTECTIVE EQUIPMENT



PROTECTIVE CLOTHING

PROTECTIVE GLASSES WITH

SIDE SHIELDS OR GOGGLES



NITRILE

GLOVES



VOC: 0% (minus exempt compounds)

DESCRIPTION:

APOC Polyset Multipurpose Cleaner is a cleaning solvent used to dissolve uncured polyurethane foam and adhesive.

PREPARATION:

Completely read all application instructions and wear proper personal protective equipment.

PERSONAL PROTECTIVE EQUIPMENT (PPE):

Recommend only in a well-ventilated area. Wear protective glasses with side shields or goggles, protective gloves, and clothing that protects against dermal exposure. Read all instructions and safety information prior to use. Consult the product's SDS (available at www.APOC.com).

GENERAL CLEANING INSTRUCTIONS:

- Removes uncured overspray or drips on solvent-resistant surfaces.
- Test a small area to ensure the cleaner will not damage the surface.
- Use only in a well ventilated area.
- Do not use in horizontal position.
- Insert red spray activator onto the valve stem of the can.
- With activator pointing towards surface to be cleaned, slowly depress red activator to spray solvent.

STORAGE & HANDLING:

Keep away from heat/sparks/open flames/hot surfaces- No Smoking. Do not spray on open flame or other ignition source. Do not puncture, incinerate, or store can above 122°F (50°C). Do not breathe mist, vapors or spray. Avoid contact with eyes and skin. Wear protective glasses or goggles, nitrile gloves, and clothing that protects against exposure. Only use in a well-ventilated area.

DISPOSAL:

Do not incinerate containers. Relieve containers of any remaining pressure and solvent before discarding. Always wear PPE during the disposal process Always dispose of empty cylinders in according to applicable federal, state, provincial and local regulations.

WARRANTY AND DISCLAIMER:

Refer to each product's TDS for specifications, testing results, and other attributes. The customer is ultimately responsible for deciding whether products and associated TDS information are appropriate for customer's use. For professional use only. Building practices unrelated to materials can lead to potential mold issues. Material suppliers cannot provide assurance that mold will not develop in any specific system. Product uses a non-flammable compressed gas. Keep away from heat. Smoking and open flames, including hot work, should be prohibited in the vicinity of a foaming operation. Avoid contact with skin and eyes. May cause sensitization by inhalation and/or direct skin contact. Persons previously sensitized to lsocyanates may develop a cross-sensitization reaction to other isocyanates. Avoid prolonged or repeated breathing of vapor. Use in conformance with all local, state and federal regulations and safety requirements. Failure to strictly adhere to any recommended procedures and reasonable safety precautions shall release ICP Building Solutions Group of all liability with respect to the materials or the use thereof. For additional information and location of your nearest distributor, call ICP Group 330.753.4585.

PRODUCT NUMBER	CONTENTS	NET WEIGHT
62484448303	Acetone and carbon dioxide	11.5 oz. (413 ml) (326 g)

