



Pro-Lastic® SBS Modified Flashing Cement

DATA SHEET

COMPLIANCE: Exceeds performance requirements of ASTM D3409 and ASTM D4586, TYPE I. MIAMI-DADE APPROVED. ASBESTOS FREE.

DESCRIPTION: APOC® 133 Pro-Lastic® SBS Modified Flashing Cement is a professional grade, polymer modified flashing cement specially formulated for use with modified bitumen membranes, base sheets and ply sheets. APOC 133 is manufactured using select asphalt, rubber, solvent and fibers. It provides excellent elongation and recovery properties plus enhanced adhesive properties and durability. It is ideal for seams, flashings and repairs on SBS modified membranes as well as conventional built up roofing. APOC 133 Pro-Lastic also contains special surfactants which push water away and allow for bonding to damp, wet or under water surfaces. Finally, use of APOC 133 eliminates burn hazards associated with hot kettles and propane torches, and is ideal where their use is prohibited. NOTE: This product is formulated for repairs and seams on SBS Asphalt Modified Roll Roofing Sheets. DO NOT use on TPO, EPDM, PVC or other single ply membranes.

PREPARATION: All surfaces must be clean, have proper drainage and free of surface rust, dust and any other foreign matter. Excessive particulate surfacing materials on modified membranes must be removed (sweeping with a stiff broom is recommended) prior to application. After a minimum of 45 days cure time, apply a reflective roof coating. This will greatly extend the life of the cement.

FOR BEST RESULTS: Apply when surface temperatures are between 50 °F and 120 °F. In colder weather product should be stored in heated room (65 °F to 80 °F.) at least 24 hours prior to application. Product formulated to be used year round.

APPLICATION: For exterior use only. Protective clothing, gloves, and eyewear should be used during application of this product. Apply with trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Using the "3-course" method, apply cement 1/8" thick, two or three inches beyond the problem area. Then reinforce the repair and embed a strip of APOC 483 polyester, APOC fiberglass or APOC cotton reinforcing fabric. Brush fabric to ensure it is fully saturated from the bottom side up. Finally, cover the fabric with an additional layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. For best results, protect completed repair with a reflective coating. Coverage rate is approximately 12 1/2 sq. ft. per gallon when applied 1/8" thick.

STORAGE & HANDLING PRECAUTIONS: When transporting this product, ensure that lid is tight and pail is secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. Do not heat or thin. Seal container when not in use.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

©2010 Gardner-Gibson, Inc.
Manufactured by / Fabricado por:
Gardner-Gibson, Inc.
P.O. Box 5449, Tampa, FL 33675

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.0 - 9.0 lbs.
Application Tools	Trowel
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container)

1 gallon (3.8L)	9 lbs.
3 gallons (11.4L)	27 lbs.
5 gallons (18.9L)	45 lbs.

VOC: <250 g/L (regulatory)

HANDLING PRECAUTIONS: Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use and for physical and health hazard information. Material safety data sheets are available on the APOC website at www.apoc.com. You can also obtain a copy from your local APOC Distributor or APOC sales representative.

LIMITED WARRANTY: APOC hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance at the time the product is manufactured. Should a manufacturing defect materially and adversely affect this product's performance, APOC shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover labor or installation costs, leaks, fastener penetrations or other holes in the membrane, exposure over 180 days, low slope roofs or materials not manufactured by APOC, consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to APOC, c/o Warranty Claims Department, P.O. Box 5449, Tampa, FL 33675. The exclusive venue for any legal action arising out of the purchase of this product or this warranty shall be had in a court of competent jurisdiction within Hillsborough County, Florida. Florida law shall govern. For additional Standard Limited Warranty information, visit www.apoc.com/pages/warranty.