

ROOFSLOPE[®]
AUXILIARY SLOPING COMPOUND



APOC[®]
professional protection™



**ELIMINATE
PONDING
WATER**





**ELIMINATES
PONDING WATER**
ACHIEVES POSITIVE
SLOPE TO AID IN
PROPER DRAINAGE



**SUPERIOR
BOND STRENGTH**
BONDS TO A WIDE VARIETY
OF ROOF SUBSTRATES:
SINGLE-PLY, GRANULATED,
COATED, CONCRETE
& MORE



**QUICK & EASY
APPLICATION**
SAVES ON TIME
AND LABOR COSTS

ROOFSLOPE[®]

AUXILIARY SLOPING COMPOUND

The RoofSlope auxiliary sloping compound provides a quick and easy way to fill in low spots on flat roofs and achieve positive slope to aid in proper drainage. This patented technology provides a durable finish with the ability to match existing roofing compositions. The RoofSlope compound is excellent for new construction as well as retrofit work, minimizing costs associated with fixing slope-to-drain issues.

SYSTEM BENEFITS:

- Cost Effective
- Fast Drying
- Extremely Durable
- Easy to Install
- Tremendous Bond Strength
- Monolithic
- Water-Based
- UV Stable
- Ability to Match a Variety of Roof Finishes
- Patented Technology

SUBSTRATES:

- Mineral Surface/Granulated
- Coated Roofs
- Single-Ply
- Concrete & More



1.**CLEAN****2.****APPLY****3.****BROADCAST****PRODUCT WEIGHT & COVERAGE**

AVERAGE PRODUCT THICKNESS	WEIGHT PER SQ. FT.	BATCH MIX	BATCH MIX COVERAGE RATE	AGGREGATE NEEDED
1/4"	2.5 lbs.	1 5Gal pail 1 1/4 Gal. Water	30 sq. ft.	1 bag/pail for every 3-4 pails of RoofSlope
1/2"	5 lbs.		15 sq. ft.	
3/4"	7.5 lbs.		11.25 sq. ft.	
1"	10 lbs.		7.5 sq. ft.	
1 1/2"	15 lbs.		5.5 sq. ft.	
2"	20 lbs.		3.75 sq. ft.	

The above weights are estimates. Actual weights will vary. For lightweight products, please contact APOC for details.

The information herein is provided as a courtesy and for evaluation only and APOC makes no warranty, express or implied, as to its accuracy or completeness or the results to be obtained therefrom. The products and information set forth in this literature are subject to change without notice and APOC disclaims all liability for such changes. Buyer is solely responsible for determining whether the products are suitable for Buyer's intended use. All product sales are subject to APOC'S Terms and Conditions of Sale. APOC DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. IN NO EVENT WILL APOC BE LIABLE FOR ANY INCIDENTAL, INDIRECT OR CONSEQUENTIAL DAMAGES ARISING FROM THE SALE OR USE OF ANY PRODUCT.

FREQUENTLY ASKED QUESTIONS

DO I NEED TO USE A PRIMER?

A primer is NOT necessary over mineral surfaced membranes and acrylic/elastomeric coated roofs. An additional step is required when installing RoofSlope over single ply, asphaltic non-granulated or non-sanded membranes, please contact APOC for additional information.

I AM CONCERNED ABOUT THE WEIGHT, IS THERE ANYTHING I CAN DO?

In general, weight has not been an issue with RoofSlope, refer to the product weight and coverage chart. To reduce weight, EPS can be used as a filler. Contact APOC for additional information.

WHY IS IT MANDATORY TO BROADCAST 16 GRIT SAND OR GRANULES INTO THE PRODUCT?

It is an integral part of ensuring the product will cure properly and minimize shrinkage cracking in the process. This is MANDATORY and should be broadcast immediately into the wet RoofSlope prior to setting it up. The granules or sand should be spread until refusal.

HOW LONG DOES THE ROOFSLOPE PRODUCT TAKE TO CURE?

Cure times will vary based on temperature and product thickness. Installations that are 3/4" or less, applied in warm weather, should be fully cured within 24 hours. If a non-breathable product is being installed over RoofSlope, ensure that a moisture meter is used in order to conform to manufacturer's requirements.

HOW THICK CAN I BUILD THE ROOFSLOPE PRODUCT IN ONE APPLICATION & HOW THIN CAN IT BE TAPERED TO?

RoofSlope has been successfully installed up to 6" thick and tapered to zero in one installation.

WHAT OTHER APPLICATIONS AND SUBSTRATES CAN THE PRODUCT BE USED FOR?

The RoofSlope product has a wide range of uses: Pitch pan filler, HVAC crickets, decks, plywood, concrete repair, blistering/damaged foam roofs, sidewalks, beneath waterproof membranes and more.

IS ROOFSLOPE WATERPROOF?

RoofSlope is water resistant, not waterproof. Roof repair should be performed before the RoofSlope compound is installed.

DOES THE ROOFSLOPE PRODUCT NEED TO BE ROOFED OR COATED OVER?

No, but you certainly can.

HOW DO I ESTIMATE THE NUMBER OF PAILS I NEED FOR A JOB?

Determine the average depth of the ponded area and the square footage. One pail of RoofSlope goes approximately 30 sq ft. @ 1/4" thick. Please order accordingly. You will need 1 bag/pail of 16 grit sand or granules per every 3-4 pails of Roof Slope. Please refer to the product weight and coverage chart.



150 Dascomb Rd., Andover, MA 01810 • 1.866.667.5119 • icpgroup.com
©2023 APOC and other marks on this brochure are trademarks of ICP Group.
9.27.23 RS0001



888-891-3536 ■ www.apoc.com ■ info@icpgroup.com