Safety Data Sheet



Section 1 - Product and Company Identification

Material Name * APOC 248 White Elastomeric Roof Coating

Product Code * AP-248, Product * White Liquid.

Description

Manufacturer * Gardner Gibson

4701 E. 7th Avenue Tampa, FL 33605 United States

www.gardner-gibson.com

Please use "Contact Us" form on the website

Telephone

 Technical
 * 813-248-2101

 Emergency
 * 800-424-9300

 Emergency
 * 703-527-3887

 Preparation Date
 * 9/25/2015

 Last Revision Date
 * 9/25/2015

Section 2 - Hazards Identification

Emergency Overview

WARNING

Causes mild skin irritation. Harmful if swallowed.

Prevention Do not handle until all safety precautions have been read and understood. Use personal

protective equipment as required. Wash thoroughly after handling.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Storage/Disposal Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in

accordance with local, regional, national, and/or international regulations.



CAUTION - May cause eye and skin irritation on contact.

Physical Form

* Liquid

Color

* White Liquid.

Odor

* Acrylic Paint-Like Odor.

Flash Point

* > 247 F(> 119.4444 C)

OSHA

* Irritant, Carcinogen

WHMIS

* Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



GHS

* Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation - Category 2A



Potential Health Effects

Inhalation

Acute (Immediate)

* Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic (Delayed)

* Under normal conditions of use, no health effects are expected.

Skin

Acute (Immediate)

* May cause irritation.

Chronic (Delayed)

* Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

Acute (Immediate)

* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.

Chronic (Delayed)

* Direct contact may cause slight to moderate irritation.

Ingestion

Acute (Immediate)

* May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.

Chronic (Delayed)

* Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

Carcinogenic Effects					
CAS IARC NTP					
Titanium Dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity		

Section 3 - Composition/Information on Ingredients

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acrylic Polymer Solution		35% TO 45%			
Calcium carbonate	EINECS: 215-279-6	25% TO 35%			
Titanium Dioxide	EINECS: 236-675-5	15% TO 25%			
Hydroxyethylcellulose		0.1% TO 0.5%			
Propylene Glycol	EINECS: 200-338-0	0.25% TO 1%	Ingestion/Oral-Rat LD50 · 20 g/kg		
Surfactant/Additive		0.25% TO 1%			
Texanol Ester	EINECS: 246-771-9	0.1% TO 1%	Ingestion/Oral-Rat LD50 · 3200 mg/kg		

Non-Hazardous Components						
Chemical Name	ical Name Identifiers %(weight) LD50/LC50 Classifications According to Regulation/Directive Comment					
Water	EINECS: 231-791-2	25% TO 45%				

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

Inhalation * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If signs/symptoms continue, get medical attention.

Skin * Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing.

If skin irritation occurs: Get medical advice/attention.

Eye * If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion * If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Section 5 - Fire Fighting Measures

Extinguishing Media * LARGE FIRE: Water spray, fog or regular foam.

SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable **Extinguishing Media** * No data available.

Firefighting Procedures * Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

Keep unauthorized personnel away.

Unusual Fire and **Explosion Hazards** * Product containers may rupture when exposed to extreme heat. Precaustions should be taken to prevent release of materials.

Products

Hazardous Combustion * Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.

Protection of **Firefighters**

* Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is

possible.

Flash Point * > 247 F(> 119.4444 C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions

* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

* Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.

Environmental Precautions

* Avoid run off to waterways and sewers.

Containment/Clean-up Measures

* Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Use appropriate Personal Protective Equipment (PPE)

Prohibited Materials

* Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

Handling

* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use.

Storage

* Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place.

Special Packaging Materials Incompatible Materials or Ignition Sources

* Not Applicable.

* Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms







Respiratory

* When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eve/Face

* Wear ANSI approved safety glasses with side shields or safety goggles.

Hands

* Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls

* Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

Exposure Limits/Guidelines						
	Result	Canada Ontario	Mexico	NIOSH	OSHA	
Propylene Glycol (57-55-6)	TWAs	50 ppm TWAEV (total aerosol and vapour); 155 mg/m3 TWAEV (total aerosol and vapour); 10 mg/m3 TWAEV (for assessing the visibility in a work environment, aerosol only)	Not established	Not established	Not established	
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	Not established	15 mg/m3 TWA (total dust)	
Calcium carbonate (1317-65-3)	TWAs	Not established		10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)	

Section 9 - Physical and Chemical Properties

Material Description			
Physical Form	Liquid	Appearance/Description	White liquid with the consistency of paint.
Color	White Liquid.	Odor	Acrylic Paint-Like Odor.
Taste	No data available.	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	No data available		
General Properties	-	-	-
Boiling Point	212 to 245 F(100 to 118.3333 C)	Melting Point	No data available
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant
рН	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.393 Water=1
Density	11.61 lbs/gal @ 25 C(77 F)	Bulk Density	No data available
Water Solubility	Soluble 100 % @ 25 C(77 F)	Solvent Solubility	Not relevant
Viscosity	115 - 120 Krebs-Stormer (KU) @ 25 C(77 F)		
Volatility	-	-	
Vapor Pressure	0.1 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1
Evaporation Rate	< 1 Ether = 1	VOC (Wt.)	No data available
VOC (Vol.)	< 45 g/L	Volatiles (Wt.)	No data available
Volatiles (Vol.)	No data available		
Flammability			
Flash Point	> 247 F(> 119.4444 C)	Flash Point Test Type	CC (Closed Cup)
UEL	No data available	LEL	No data available
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant
Flame Duration	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
Environmental			
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant
Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant
Degradation	Not relevant		

Section 10 - Stability and Reactivity

Stability

* Stable under normal temperatures and pressures.

Hazardous Polymerization

* Hazardous polymerization not indicated.

Conditions to Avoid

* Excessive heat and freezing.

Incompatible Materials

Hazardous Decomposition

* Strong oxidizers and acids.

Products

* No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data
Water (25% TO 45%)	7732-18-5	Acute Toxicity: orl-rat LD50:>90 mL/kg
Titanium Dioxide (15% TO 25%)		Acute Toxicity: orl-rat TDLo:60 gm/kg; Irritation: skn-hmn 300 ug/3D-I MLD
Propylene Glycol (0.25% TO 1%)	57-55-6	Acute Toxicity: orl-rat LD50:20 gm/kg; skn-hmn TCLo:10 pph; skn-hmn TDLo:5 mg/kg/7D-l; lrritation: skn-hmn 500 mg/7D MLD
Texanol Ester (0.1% TO 1%)	25265-77-4	Acute Toxicity: orl-rat LD50:3200 mg/kg; ihl-rat LC :>3500 mg/m3/6H

Information

Other Component * IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans(Group 2B): Titanium Dioxide. Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

Section 12 - Ecological Information

Ecological Fate

* No data available.

Persistence/Degradability

* No data available.

Bioaccumulation Potential

* No data available.

Mobility in Soil

* No data available.

Other Information

* Do not allow product exposure to the ground or into any waterway. Do not allow

entry into muncipal sewer systems.

Section 13 - Disposal Considerations

Product

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

State Right To Know					
Component	CAS	MA	MN	NJ	PA
Water	7732-18-5	No	No	No	No
Acrylic Polymer Solution	NDA	No	No	No	No
Calcium Carbonate	1317-65-3	Yes	Yes	Yes	Yes
Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
Hydroxyethylcellulose	9004-62-0	No	No	No	No
Propylene Glycol	57-55-6	No	Yes	Yes	Yes
Surfactant/Additive	NDA	No	No	No	No
Texanol Ester	25265-77-4	No	No	No	No

Inventory					
Component	CAS	EU EINECS	TSCA		
Water	7732-18-5	Yes	Yes		
Acrylic Polymer Solution	NDA	No	No		
Calcium Carbonate	1317-65-3	Yes	Yes		
Titanium Dioxide	13463-67-7	Yes	Yes		
Hydroxyethylcellulose	9004-62-0	No	Yes		
Propylene Glycol	57-55-6	Yes	Yes		
Surfactant/Additive	NDA	No	No		
Texanol Ester	25265-77-4	Yes	Yes		

Canada

Labor

Canada - WHMIS - Classifications of Substances

•Calcium Carbonate 1317-65-3 25% TO 35% D2A

D2A (In certain cases, this classification does not apply. For more information,

•Titanium Dioxide 13463-67-7 15% TO 25% consult the section Substance Specific Issues - Titanium dioxide, mixture containing

on Health Canada's WHMIS website.)

Propylene Glycol
 Texanol Ester
 Uncontrolled product according to WHMIS classification criteria
 Uncontrolled product according to WHMIS classification criteria
 Hydroxyethylcellulose
 0.1% TO 1%
 Uncontrolled product according to WHMIS classification criteria
 Uncontrolled product according to WHMIS classification criteria

11-24-1-04-4--

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Calcium carbonate
 Titanium Dioxide
 Propylene Glycol
 Texanol Ester
 Hydroxyethylcellulose
 Talef-6-3
 25% TO 35%
 Not Listed
 Not Listed
 0.25% TO 1%
 Not Listed
 Not Listed
 Not Listed
 Not Listed
 Not Listed
 Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

Calcium carbonate
 Titanium Dioxide
 Propylene Glycol
 Texanol Ester
 Hydroxyethylcellulose
 1317-65-3
 20% TO 30%
 Not Listed
 Not Listed
 0.25% TO 1%
 Not Listed
 Not Listed
 Not Listed
 10.1% TO 1%
 Not Listed
 Not Listed
 Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

 • Calcium carbonate
 1317-65-3
 25% TO 35%
 Toxic

 • Titanium Dioxide
 13463-67-7
 15% TO 25%
 Toxic

 • Propylene Glycol
 57-55-6
 0.25% TO 1%
 Combustible

 • Texanol Ester
 25265-77-4
 0.1% TO 1%
 Not Listed

 • Hydroxyethylcellulose
 9004-62-0
 0.1% TO 1%
 Not Listed

Other Information * WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date

* 9/25/2015

Last Revision Date Disclaimer/Statement of Liability

* 9/25/2015

* This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.