Safety Data Sheet



Section 1 - Product and Company Identification

Material Name * APOC 290 Self Bond SA Primer

Product Code * AP-2901/2905. AP560/5601/5605

Product Description

* White Liquid.

Product Use

* Primer

Synonyms * Roof Base Coat

Manufacturer * Gardner Gibson

4701 E. 7th Avenue Tampa, FL 33605 United States

www.gardner-gibson.com

Please use "Contact Us" form on the website

Telephone

 Technical
 * 813-248-2101

 Emergency
 * 800-424-9300

 Emergency
 * 703-527-3887

Preparation Date * 11/8/2015 Last Revision Date * 11/8/2015

Section 2 - Hazards Identification

Emergency Overview

WARNING

Causes mild skin irritation. Harmful if swallowed.

Prevention Do not handle until all safety precautions have been read and understood. Use personal

protective equipment as required. Wash thoroughly after handling.

Response IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.

Storage/Disposal Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in

accordance with local, regional, national, and/or international regulations.



CAUTION - May cause eye and skin irritation on contact.

Physical Form

* Liquid

Color

* White Liquid.

Odor

* Acrylic Paint-Like Odor.

Flash Point

* > 247 F(> 119.4444 C)

OSHA

* Irritant

WHMIS

Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B



GHS

* Skin Corrosion/Irritation - Category 3, Serious Eye Damage, Eye Irritation -Category 2A



Potential Health Effects

Inhalation

Acute (Immediate) * Inhalation of vapors or mists may cause central nervous system depression, lightheadedness, headache, nausea and loss of coordination.

Chronic (Delayed) * Under normal conditions of use, no health effects are expected.

Skin

Acute (Immediate) * May cause irritation.

Chronic (Delayed) * Repeated and prolonged exposure to the skin may cause dermatitis.

Eye

Acute (Immediate)

* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.

Chronic (Delayed)

* Direct contact may cause slight to moderate irritation.

Ingestion

Acute (Immediate) * May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.

Chronic (Delayed) * Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

Carcinogenic Effects						
	CAS IARC NTP					

Section 3 - Composition/Information on Ingredients

Hazardous Components						
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments	
Acrylic Polymer Solution	CAS: 25085-34-1	<60.0%				
Propylene Glycol	CAS: 57-55-6	1.0%	Ingestion/Oral-Rat LD50 · 20 g/kg			

Non-Hazardous Components							
Chemical Name	Chemical Name Identifiers %(weight) LD50/LC50 Classifications According to Regulation/Directive Comments						

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Section 4 - First Aid Measures

Inhalation * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing. If signs/symptoms continue, get medical attention.

* Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. Skin

If skin irritation occurs: Get medical advice/attention.

* If eye irritation persists: Get medical advice/attention. IF IN EYES: Rinse cautiously with water Eve

for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion * If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Section 5 - Fire Fighting Measures

* LARGE FIRE: Water spray, fog or regular foam. **Extinguishing Media**

SMALL FIRES: Dry chemical, CO2, water spray or regular foam.

Unsuitable * No data available.

Extinguishing Media

Firefighting Procedures * Fire fighters should wear complete protective clothing including self-contained breathing

apparatus.

Keep unauthorized personnel away.

Unusual Fire and **Explosion Hazards** * Product containers may rupture when exposed to extreme heat. Precaustions should be

taken to prevent release of materials.

Products

Hazardous Combustion * Non-combustible, substance itself does not burn but may decompose upon heating to

produce toxic fumes.

Protection of Firefighters

* Structural firefighters' protective clothing provides limited protection in fire situations

ONLY; it is not effective in spill situations where direct contact with the substance is

possible.

Flash Point * > 247 F(> 119.4444 C) CC (Closed Cup)

Section 6 - Accidental Release Measures

Personal Precautions

* Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

* Isolate the area and contain the spilled material. Persons not wearing the appropriate

PPE should be removed from the area until the spill is cleaned up.

Environmental **Precautions**

* Avoid run off to waterways and sewers.

Containment/Clean-up Measures

* Absorb or cover with dry earth, sand or other non-combustible material and transfer to

containers.

Use appropriate Personal Protective Equipment (PPE)

Prohibited Materials * Avoid contact with strong oxidizing agents and acids.

Section 7 - Handling and Storage

* KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed Handling when not in use.

Storage * Avoid extreme temperatures and freezing. Keep container/package tightly

closed and in a well-ventilated place.

Special Packaging Materials Incompatible Materials or Ignition Sources

* Not Applicable.

* Avoid contact with strong oxidizing agents and acids.

Section 8 - Exposure Controls/Personal Protection

Personal Protective Equipment

Pictograms







Respiratory

* When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Eye/Face

* Wear ANSI approved safety glasses with side shields or safety goggles.

Hands

* Wear chemical resistant gloves with repeated or prolonged exposure.

Engineering Measures/Controls * Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

	Exposure Limits/Guidelines							
	Result	Canada Ontario	Mexico	NIOSH	OSHA			
Propylene Glycol (57-55-6)	TWAs	50 ppm TWAEV (total aerosol and vapour); 155 mg/m3 TWAEV (total aerosol and vapour); 10 mg/m3 TWAEV (for assessing the visibility in a work environment, aerosol only)	Not established	Not established	Not established			

Section 9 - Physical and Chemical Properties

Material Description					
Physical Form	Liquid	Appearance/Description	White liquid with heavy consistency.		
Color	White Liquid.	Odor	Acrylic Paint-Like Odor.		

Taste	No data available.	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	No data available		
General Properties			
Boiling Point	212 to 245 F(100 to 118.3333 C)	Melting Point	No data available
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant
рН	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.04 Water=1
Density	8.67 lbs/gal @ 25 C(77 F)	Bulk Density	No data available
Water Solubility	Soluble 100 % @ 25 C(77 F)	Solvent Solubility	Not relevant
Viscosity	110-105 KU. @ 25 C(77 F)		
Volatility	•	-	
Vapor Pressure	0.1 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1
Evaporation Rate	< 1 Ether = 1	VOC (Wt.)	No data available
VOC (Vol.)	27 g/L	Volatiles (Wt.)	No data available
Volatiles (Vol.)	No data available		
Flammability			
Flash Point	> 247 F(> 119.4444 C)	Flash Point Test Type	CC (Closed Cup)
UEL	No data available	LEL	No data available
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant
Heat of Combustion (ΔHc)	Not relevant	Burning Time	Not relevant
Flame Duration	Not relevant	Flame Height	Not relevant
Flame Extension	Not relevant	Ignition Distance	Not relevant
Environmental	•	-	
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant
Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant
Degradation	Not relevant		

Section 10 - Stability and Reactivity

Stability

* Stable under normal temperatures and pressures.

Hazardous Polymerization

* Hazardous polymerization not indicated.

Conditions to Avoid Incompatible Materials

* Excessive heat and freezing.

Hazardous Decomposition

* Strong oxidizers and acids.

Products

* No known issues under normal usage conditions.

Section 11 - Toxicological Information

Component Name	CAS	Data
Propylene Glycol	57-55-6	Acute Toxicity: orl-rat LD50:20 gm/kg; skn-hmn TCLo:10 pph; skn-hmn TDLo:5 mg/kg/7D-I; Irritation: skn-hmn 500 mg/7D MLD

Other Component Information

^{*} IARC has concluded that none of the following chemicals in this product are carcinogenic to humans.

Section 12 - Ecological Information

Ecological Fate * No da

Persistence/Degradability * No da

* No data available.

Piecesumulation Potential

* No data available.

Bioaccumulation Potential

* No data available.

Mobility in Soil

* No data available.

Other Information

* Do not allow product exposure to the ground or into any waterway. Do not allow

entry into muncipal sewer systems.

Section 13 - Disposal Considerations

Product

* Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transportation Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated.

TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.

IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated.

IATA - International Air Transportation Association - Not Regulated.

Section 15 - Regulatory Information

SARA Hazard Classifications * Acute, Chronic

State Right To Know						
Component CAS MA MN NJ PA						
Acrylic Polymer Solution	25085-34-1	No	No	No	No	
Propylene Glycol	57-55-6	No	Yes	Yes	Yes	

Inventory						
Component	CAS	EU EINECS	TSCA			
Acrylic Polymer Solution	25085-34-1	No	No			
Propylene Glycol	57-55-6	Yes	Yes			

Canada

Labor

Canada - WHMIS - Classifications of Substances

Propylene Glycol 57-55-6 Uncontrolled product according to WHMIS classification criteria

United States

Environment

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

•Propylene Glycol 57-55-6 Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

• Propylene Glycol 57-55-6 Combustible

Other Information

* WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Preparation Date * 11/8/2015

Last Revision Date Disclaimer/Statement

Disclaimer/Statement of Liability

* 11/8/2015

* This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. Gardner-Gibson does not accept liability for any loss or damage that may occur from the use of this information.