

TUFF-GRIP™ 15

SYNTHETIC ROOF UNDERLAYMENT



APOC

professional protection™



PREMIUM WEATHER PROTECTION

PROTECTS AGAINST
DESTRUCTIVE ELEMENTS



TUFF-GRIP COATING TECHNOLOGY

ENHANCED GRIP TO DECK
BEFORE FASTENING FOR SAFER,
FASTER INSTALL



HIGH-TRACTION SURFACE

OUTSTANDING WALKABILITY ON
STEEP SLOPE ROOF SURFACES



ENHANCED 90 DAY UV RESISTANCE

WITHSTANDS DIRECT
SUNLIGHT EXPOSURE WITHOUT
DEGRADATION



20 YEAR
EXTENDED
WARRANTY



TUFF-GRIP™ 15

SYNTHETIC ROOF UNDERLAYMENT

APOC TUFF-GRIP™ 15 is a UV-stabilized polypropylene underlayment designed to shed water. It provides a secondary layer of protection against wind, moisture, and other elements and replaces the use of #15 and #30 organic roofing felt under asphalt shingles, residential metal and cedar shake roofing materials.

Designed with a high-traction, slip-resistant surface, TUFF-GRIP™ enhances safety and productivity—even on steep slopes. Its UV-resistant composition provides reliable protection during extended exposure, while its lightweight yet robust construction ensures superior defense against moisture, wind, and harsh weather.

FEATURES:

- **TUFF-GRIP™ Coating Technology:** Securely grips to the roof deck before fastener application, ensuring easier and safer installation.
- **High-Traction Surface:** Delivers outstanding walkability, even on steep, wet or slick surfaces.
- **All-Temperature, All-Weather Performance:** Remains flexible in extreme conditions—from -40°F to 240°F.
- **Premium Weather Protection:** Shields against wind-driven rain and moisture infiltration.
- **Extended UV Resistance:** Withstands up to 90 days of direct sunlight exposure without degradation.
- **Durable Performance:** Tough synthetic construction resists tears, punctures, and stretching.
- **Lightweight Design:** Easier to handle and install, improving job site efficiency.
- **Long-Term Assurance and Reliability:** Backed by a robust 20-year limited warranty.
- **Wider Coverage:** 48" width for faster, more efficient installs.

SHIELD YOUR ROOF WITH CONFIDENCE.



FL APPROVED

MEETS

ASTM E109

MEETS

USES:

APOC TUFF-GRIP™ 15 is a cost effective roofing underlayment used beneath fiberglass and asphalt shingles, shakes, stone-coated steel roofing shingles, synthetic slate or sloped installations of standing seam metal panels.

PRODUCT SPECS:

PRODUCT CODE	AP-6400-15
DIMENSIONS	48" X 250'
MATERIAL PER ROLL (EXCLUDES LAPS)	1,000 Sq.ft. 10 Squares
APPROXIMATE ROLL WEIGHT	17.4 lb

SEE TDS ON APOC.COM FOR ADDITIONAL PRODUCT DATA

COMPLIANCE & CODES:

- Intertek Code Compliance Research Report CCRR-0604
- Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
- Performance characteristics meet or exceed ASTM D226 – Type I, II
- Meets the requirements of ICC-AC-188
- FBC Approved - #FL47536
- UL Classified ASTM E108 (Class A)

ABOUT APOC

APOC is a premier brand for roofing, waterproofing and maintenance products that maximize productivity, performance and energy efficiency. ICP is a global producer with local manufacturing, support and customer service and is proud to be headquartered in the USA. When you offer APOC coatings, adhesives, sealants and construction products, you get more than just quality products. We're your one-stop shop for the widest range of product solutions, training and support to deliver value to your customers on time, on budget and beyond expectations.

CONTACT US:
www.apoc.com | 888-891-3536



START GETTING REWARDED FOR YOUR LOYALTY

**SIGN UP AND
START EARNING!**

Scan QR code or go to
www.awardlink.com/icp



APOC® CONTRACTOR PRO PROGRAM

QUALIFY FOR VARIOUS REWARDS

- Points for purchase
- Company recognition
- Free swag
- Marketing support
- And more!



4161 East 7th Avenue, Tampa, Florida 33605 | www.icpgroup.com
©2025 APOC and other marks on this brochure are trademarks of ICP Group.
H-25 TG15

888-891-3536
www.apoc.com

